

L5 ANSWER 61 OF 575 CA COPYRIGHT 2004 ACS on STN  
 AN 136:89781 CA  
 ED Entered STN: 31 Jan 2002  
 TI Polymer-**cement slurry** for decorative finishing of  
 buildings  
 IN Khrulev, V. M.; Plastunov, A. G.; Ottochko, O. D.; Kolesnikov, A. F.  
 PA Novosibirskii Gosudarstvennyi Arkhitekturno-Stroitel'nyi Universitet,  
 Russia  
 SO Russ., No pp. given  
 CODEN: RUXXE7  
 DT Patent  
 LA Russian  
 IC ICM C04B026-02  
 ICS C04B026-04; C04B028-04; C04B028-06  
 CC 58-3 (Cement, Concrete, and Related Building Materials)  
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
	-----	---	-----	-----	-----
PI	RU 2157796	C1	20001020	RU 1999-116199	19990727
PRAI	RU 1999-116199		19990727		
AB	The <b>slurry</b> comprises a mineral binder 25-35, filler (e.g., quartz sand, slag sand, or marble sand) 47-65, stabilized synthetic latex SKS 65GP 3.2-7 wt.%, and <b>water</b> in the balance. The mineral binder contains ground high-calcium <b>fly ash</b> 45-50, portland <b>cement</b> 30-40, and low fired clay powder 15-20 wt.%. The <b>slurry</b> exhibit better decorative properties, improved adhesion strength to concrete and compressive strength.				
ST	<b>cement</b> mortar <b>fly ash</b> clay latex decoration finishing				